

Basic infrared thermometer ThermoLaser TMTL 500

Measuring temperature at a safe distance

Lightweight and compact, the ThermoLaser utilises advanced class II laser beam for accurate aiming and an infrared detector for measuring temperature. The ThermoLaser is extremely user-friendly - simply aim, pull the trigger and read the temperature on the large backlit display. No contact with hot surfaces or moving parts means safer, faster and easier temperature measurement. Additionally, the ThermoLaser allows temperature measurement where contact with a conventional temperature probe should be avoided to prevent surface contamination, making ideal to use for measuring temperature of food processing applications.



- Safely measures the temperature of hot, hazardous or hard-to-reach objects
- Wide measurement range from -60 to 500 °C (-76 to 932 °F)
- Distance/spot ratio of 11:1, better for applications where accuracy is critical
- Ideal complement to other condition monitoring techniques, such as vibration analysis
- Backlit display, making temperature easier to read in dimly lit or dark places
- Temperature reading selection in °C or °F
- Low power consumption using 2x AAA batteries, more energy efficient
- Auto shut off feature, to optimise battery life
- Robust construction for use in an industrial environment

Technical data

Designation	TMTL 500
Temperature range	-60 to 500 °C (-76 to 932 °F)
Environmental limits	Operation 0 to 50 °C (32 to 120 °F) 10 to 95% R.H. Storage - 20 to 65 °C (-4 to 150 °C) 10 to 95% R.H. (Tamb = 23 +/- 3 °C) +/-2% of reading or 2 °C (whichever is greater)
Full range accuracy	500-1000 msec
Response time	500-1000 msec
Display	LCD
Displayed resolution	0.1 °C/F from -9.9-199.9, otherwise 1 °C/F
Distance to spot size	11:1
Spectral response	8-14 µm
User selectable backlit display	No, permanently on
User selectable laser pointer	No, permanently on
Emissivity	Pre-set 0.95
Laser wavelength	635 - 650 nm
Laser	Class 2
Maximum laser power	1 mW
Dimensions	175 x 72 x 39 mm (6.9 x 2.8 x 1.5 in)
Packed	Carton box
Weight	180 g (0.4lb)
Battery	2 x AAA Alkaline type IEC LR03
Battery lifetime	18 hours
Switch off	Automatic after 15 seconds after trigger is released
EMC standards	EN 61326:1997+A1+A2
Laser standards	CFR 1040-10 / 60825-1



© SKF is a registered trademark of the SKF Group
© SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

MP/PDS TMTL500 EN • October 2009

www.mapro.skf.com • skf.com/mount • skf.com/lubrication

ЗАО «БЕРГ АБ», (495) 727-22-72, promshop-biz@ya.ru, www.promshop.biz

